

MY507A

DESIGNED FOR ON/OFF HIGHWAY ALL-POSITION APPLICATIONS.



MY507A

ON AND OFF HIGHWAY

WIDE-BASE

The MY507A is designed to provide outstanding durability and performance for wide base on/off-highway applications. Equipped with the latest Yokohama technology to extend casing life in tough applications, the MY507A is the perfect choice for vehicles such as concrete mixers, dump trucks and waste/sanitation trucks.

26/32" Tread Depth
Specialized tread for long on/off-road mileage



Wide Rib Pattern
Outstanding wear & traction



LONGEVITY

Deep groove depth, combined with its **special anti-chip tread** compounding, enables the MY507A to provide long on/off-road mileage, without sacrificing durability.

EFFICIENCY

Wide, block-type rib pattern provides outstanding wear resistance, and excellent traction in mud, snow and wet conditions.

Funnel-shaped grooves increase block rigidity for added traction, enhanced resistance against uneven wear and superior ride comfort.

DEPENDABILITY

Stone ejectors in the tread grooves guard against stone penetration damage to the casing, to improve retreadability.

High strength belt construction further enhances durability for the extreme demands of on/off-highway applications.

SIZES AND SPECIFICATIONS

| Tire Size | Item No. | Std. Weight (Lbs) | Rim Width | | Inflated Dimensions | | Loaded Dimensions | | | Max. Load @ Max. PSI | | Tread Depth |
|--------------------|----------|-------------------|-----------|-------|---------------------|------------------|-------------------|-----------|---------------|----------------------|------|-------------|
| | | | Pref. | Alt. | Overall Width | Overall Diameter | Static Radius | Rev/ Mile | Section Width | Single | Dual | |
| 385/65R22.5 18J TL | 50751 | 179 | 11.75 | 11.75 | 14.9 | 42.6 | 19.7 | 492 | 16.0 | 9370 @ 120 | 0 | 23 |
| 425/65R22.5 20L TL | 50752 | 205 | 13.00 | 11.75 | 16.5 | 44.6 | 20.5 | 470 | 17.9 | 11400 @ 120 | 0 | 23 |
| 445/65R22.5 20L TL | 50753 | 221 | 13.00 | 12.25 | 17.3 | 45.7 | 21.0 | 459 | 18.9 | 12300 @ 120 | 0 | 24 |