

# SY767

A RUGGED HIGHWAY DRIVE TIRE WITH TRUE FOUR SEASON TRACTION.



The exceptional traction capabilities of the SY767 overcome wet, muddy and snowy highway conditions. Its optimum tread compound contributes to long treadlife and extended casing. With the SY767, you not only get great all-weather grip, you get great mileage too traction and durability.

**Multi-Season Rubber Compounding**  
Maximum road contact



26/32" Tread Depth

Deep Wide Grooves

## LONGEVITY

**Extra-wide tread matched with 26/32" tread depth** promotes great handling, stability and long, even wear.

**Thick under tread** provides cool running for extended casing life.

## EFFICIENCY

**Multi-season rubber compounding** is our latest compound that ensures superior grip and wear resistance.

## DEPENDABILITY

**Deep wide grooves** efficiently evacuate water to maximize contact with the road surface.

**Extensive grooving and siping** maximize biting edges for enhanced traction. Closed sipes increase traction without reducing block rigidity.

## SIZES AND SPECIFICATIONS

| Tire Size      | Item No. | Std. Weight (Lbs) | Rim Width |      | Inflated Dimensions |                  | Loaded Dimensions |           |               | Max. Load @ Max. PSI |            | Tread Depth |
|----------------|----------|-------------------|-----------|------|---------------------|------------------|-------------------|-----------|---------------|----------------------|------------|-------------|
|                |          |                   | Pref.     | Alt. | Overall Width       | Overall Diameter | Static Radius     | Rev/ Mile | Section Width | Single               | Dual       |             |
| 11R22.5 14G TL | 76702    | 129               | 8.25      | 7.50 | 10.9                | 41.9             | 19.6              | 497       | 12.1          | 6175 @ 105           | 5840 @ 105 | 26          |
| 11R22.5 16H TL | 76722    | 129               | 8.25      | 7.50 | 10.9                | 41.9             | 19.6              | 497       | 12.1          | 6610 @ 120           | 6005 @ 120 | 26          |
| 11R24.5 14G TL | 76704    | 136               | 8.25      | 7.50 | 10.9                | 43.9             | 20.5              | 475       | 12.1          | 6610 @ 105           | 6005 @ 105 | 26          |
| 11R24.5 16H TL | 76724    | 136               | 8.25      | 7.50 | 10.9                | 43.9             | 20.5              | 475       | 12.1          | 7160 @ 120           | 6610 @ 120 | 26          |